

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## 250.2103 Extra - Fix Slow (TF) All Purpose Adhesive

Print date: 07.10.2015

Product code: 250.2103

Page 1 of 12

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

250.2103 Extra - Fix Slow (TF) All Purpose Adhesive

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Use of the substance/mixture

Adhesives, sealants

Roller application or brushing of adhesive and other coating.

#### 1.3. Details of the supplier of the safety data sheet

|                         |                           |                        |
|-------------------------|---------------------------|------------------------|
| Company name:           | AFT INTERNATIONAL NV<br>B |                        |
| Street:                 | Ter Stratenweg 50         |                        |
| Place:                  | B-2520 Oelegem            |                        |
| Telephone:              | +32-34-759303             | Telefax: +32-34-759320 |
| e-mail:                 | els@aft-international.de  |                        |
| Contact person:         | Herr Speelmans            |                        |
| e-mail:                 | info@aft-international.be |                        |
| Responsible Department: | Import-Einkauf            |                        |

#### 1.4. Emergency telephone number:

+32-34-759303

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Regulation (EC) No. 1272/2008

Hazard categories:

Flammable liquid: Flam. Liq. 2

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:

Highly flammable liquid and vapour.

Causes skin irritation.

Causes serious eye irritation.

May cause drowsiness or dizziness.

Toxic to aquatic life with long lasting effects.

#### 2.2. Label elements

##### Regulation (EC) No. 1272/2008

##### Hazardous components which must be listed on the label

ethyl acetate

cyclohexane

##### Signal word:

Danger

##### Pictograms:



##### Hazard statements

H225

Highly flammable liquid and vapour.

H315

Causes skin irritation.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 250.2103 Extra - Fix Slow (TF) All Purpose Adhesive

Print date: 07.10.2015

Product code: 250.2103

Page 2 of 12

|      |  |
|------|--|
| H319 | Causes serious eye irritation.                   |
| H336 | May cause drowsiness or dizziness.               |
| H411 | Toxic to aquatic life with long lasting effects. |

#### Precautionary statements

|                |  |
|----------------|--|
| P210           | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.                                   |
| P233           | Keep container tightly closed.   |
| P235           | Keep cool.   |
| P240           | Ground/bond container and receiving equipment.   |
| P241           | Use explosion-proof electrical/ventilating/lighting equipment.   |
| P242           | Use only non-sparking tools.   |
| P243           | Take precautionary measures against static discharge.  |
| P261           | Avoid breathing dust/fume/gas/mist/vapours/spray.  |
| P264           | Wash ... thoroughly after handling.  |
| P271           | Use only outdoors or in a well-ventilated area.  |
| P273           | Avoid release to the environment.  |
| P280           | Wear protective gloves/protective clothing/eye protection/face protection.   |
| P303+P361+P353 | IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.                              |
| P304+P340      | IF INHALED: Remove person to fresh air and keep comfortable for breathing.   |
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P312           | Call a POISON CENTER/doctor if you feel unwell.  |
| P321           | Specific treatment (see ... on this label).  |
| P332+P313      | If skin irritation occurs: Get medical advice/attention.   |
| P337+P313      | If eye irritation persists: Get medical advice/attention.  |
| P352           | Wash with plenty of water.   |
| P364           | And wash it before reuse.  |
| P370+P378      | In case of fire: Use ... to extinguish.  |
| P391           | Collect spillage.  |
| P403+P233      | Store in a well-ventilated place. Keep container tightly closed.   |
| P405           | Store locked up.   |
| P501           | Dispose of contents/container to ....  |

#### Special labelling of certain mixtures

|        |  |
|--------|--|
| EUH018 | In use may form flammable/explosive vapour-air mixture.      |
| EUH066 | Repeated exposure may cause skin dryness or cracking.        |
| EUH208 | Contains Rosin, colophony. May produce an allergic reaction. |

#### Additional advice on labelling

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

#### 2.3. Other hazards

In use, may form flammable/explosive vapour-air mixture.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

##### Chemical characterization

polychloroprene adhesive with modified synthetic resins and stabilizers in a mixture of organic solvents

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 250.2103 Extra - Fix Slow (TF) All Purpose Adhesive

Print date: 07.10.2015

Product code: 250.2103

Page 3 of 12

#### Hazardous components

| CAS No     | Chemical name   |              |                  | Quantity    |
|------------|---|--------------|------------------|-------------|
|            | EC No   | Index No     | REACH No         |             |
|            | Classification according to Regulation (EC) No. 1272/2008 [CLP]   |              |                  |             |
| 64742-49-0 | Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha   |              |                  | 30 - < 35 % |
|            | 265-151-9   | 649-328-00-1 | 01-2119475514-35 |             |
|            | Flam. Liq. 2, Skin Irrit. 2, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H304 H411  |              |                  |             |
| 141-78-6   | ethyl acetate   |              |                  | 25 - < 30 % |
|            | 205-500-4   | 607-022-00-5 | 01-2119475103-46 |             |
|            | Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066  |              |                  |             |
| 110-82-7   | cyclohexane   |              |                  | 20 - < 25 % |
|            | 203-806-2   | 601-017-00-1 | 01-2119463273-41 |             |
|            | Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Acute 1 (M-Factor = 1), Aquatic Chronic 1; H225 H315 H336 H304 H400 H410 |              |                  |             |
| 8052-10-6  | Rosin, colophony  |              |                  | < 1 %       |
|            | 232-484-6   | 650-015-00-7 |                  |             |
|            | Skin Sens. 1; H317  |              |                  |             |

Full text of H and EUH statements: see section 16.

#### SECTION 4: First aid measures

##### 4.1. Description of first aid measures

###### General information

Remove affected person from the danger area and lay down.

###### After inhalation

In case of inhalation of decomposition products, affected person should be moved into fresh air and kept still.  
Remove casualty to fresh air and keep warm and at rest.

###### After contact with skin

Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap. Grease skin after contact.

###### After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

###### After ingestion

Do NOT induce vomiting. In case of allergic symptoms, especially in the breathing area, seek medical advice immediately.

##### 4.2. Most important symptoms and effects, both acute and delayed

Allergic reactions.

##### 4.3. Indication of any immediate medical attention and special treatment needed

Position and transport victim on their side. In case of respiratory distress, bring into semi-upright, seated position. Where appropriate artificial ventilation.

#### SECTION 5: Firefighting measures

##### 5.1. Extinguishing media

###### Suitable extinguishing media

alcohol resistant foam. ABC powder. Atomized water. Dry sand.

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## 250.2103 Extra - Fix Slow (TF) All Purpose Adhesive

Print date: 07.10.2015

Product code: 250.2103

Page 4 of 12

### Unsuitable extinguishing media

High power water jet. High power water jet.

### 5.2. Special hazards arising from the substance or mixture

In case of fire and/or explosion do not breathe fumes. In case of fire may be liberated: Hydrogen chloride (HCl). Burning produces heavy smoke.

### 5.3. Advice for firefighters

Special exposure hazards arising from the substance itself, combustion products, resulting gases: In case of fire: Wear self-contained breathing apparatus.

### Additional information

Use water spray jet to protect personnel and to cool endangered containers. Contaminated fire-fighting water must be collected separately. Remove product from area of fire. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Provide adequate ventilation.

### 6.2. Environmental precautions

Do not allow to enter into surface water or drains. Cover drains.

### 6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Collect in closed containers for disposal.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation should be used if possible. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

#### Advice on protection against fire and explosion

Keep away from sources of ignition. - No smoking. Only use the material in places where open light, fire and other flammable sources can be kept away. Vapours / aerosols must be extracted by suction immediately at point of origin.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep only in the original container in a cool, well-ventilated place. Keep container tightly closed. Recommended storage temperature: 15-30 °C Ensure adequate ventilation of the storage area.

#### Advice on storage compatibility

Store packaging and combustible materials separately from one another. Keep away from food, drink and animal feedingstuffs.

#### Further information on storage conditions

Floors should be impervious, resistant to liquids and easy to clean. Store small packages in a suitable, robust cabinet.

### 7.3. Specific end use(s)

Adhesives, sealants Roller application or brushing of adhesive and other coating.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 250.2103 Extra - Fix Slow (TF) All Purpose Adhesive

Print date: 07.10.2015

Product code: 250.2103

Page 5 of 12

#### Exposure limits (EH40)

| CAS No   | Substance     | ppm | mg/m <sup>3</sup> | fibres/ml | Category      | Origin |
|----------|---------------|-----|-------------------|-----------|---------------|--------|
| 110-82-7 | Cyclohexane   | 100 | 350               |           | TWA (8 h)     | WEL    |
|          |               | 300 | 1050              |           | STEL (15 min) | WEL    |
| 141-78-6 | Ethyl acetate | 200 | -                 |           | TWA (8 h)     | WEL    |
|          |               | 400 | -                 |           | STEL (15 min) | WEL    |

#### DNEL/DMEL values

| CAS No                   | Substance   | Exposure route | Effect   | Value                  |
|--------------------------|---|----------------|----------|------------------------|
| 64742-49-0               | Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha |                |          |                        |
| Worker DNEL, long-term   |   | dermal         | systemic | 13964 mg/kg bw/day     |
| Worker DNEL, long-term   |   | inhalation     | systemic | 5306 mg/m <sup>3</sup> |
| Consumer DNEL, long-term |   | dermal         | systemic | 1377 mg/kg bw/day      |
| Consumer DNEL, long-term |   | inhalation     | local    | 1137 mg/m <sup>3</sup> |
| Consumer DNEL, long-term |   | oral           | systemic | 1601 mg/kg bw/day      |
| 141-78-6                 | ethyl acetate   |                |          |                        |
| Worker DNEL, long-term   |   | inhalation     | systemic | 1468 mg/m <sup>3</sup> |
| Worker DNEL, acute       |   | inhalation     | local    | 1468 mg/m <sup>3</sup> |
| Worker DNEL, long-term   |   | dermal         | systemic | 63 mg/kg bw/day        |
| Worker DNEL, long-term   |   | inhalation     | local    | 734 mg/m <sup>3</sup>  |
| Consumer DNEL, acute     |   | inhalation     | systemic | 734 mg/m <sup>3</sup>  |
| Consumer DNEL, long-term |   | inhalation     | local    | 734 mg/m <sup>3</sup>  |
| Consumer DNEL, long-term |   | dermal         | systemic | 37 mg/kg bw/day        |
| Consumer DNEL, long-term |   | inhalation     | systemic | 367 mg/m <sup>3</sup>  |
| Consumer DNEL, long-term |   | oral           | systemic | 4,5 mg/kg bw/day       |
| Consumer DNEL, acute     |   | inhalation     | local    | 367 mg/m <sup>3</sup>  |
| 110-82-7                 | cyclohexane   |                |          |                        |
| Consumer DNEL, long-term |   | oral           | systemic | 59,4 mg/kg bw/day      |
| Consumer DNEL, long-term |   | dermal         | systemic | 699 mg/kg bw/day       |
| Worker DNEL, long-term   |   | dermal         | systemic | 2016 mg/kg bw/day      |
| Consumer DNEL, long-term |   | inhalation     | systemic | 206 mg/m <sup>3</sup>  |
| Worker DNEL, long-term   |   | inhalation     | systemic | 700 mg/m <sup>3</sup>  |

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 250.2103 Extra - Fix Slow (TF) All Purpose Adhesive

Print date: 07.10.2015

Product code: 250.2103

Page 6 of 12

#### PNEC values

| CAS No                    | Substance     |             |
|---------------------------|---------------|-------------|
| Environmental compartment |               | Value       |
| 141-78-6                  | ethyl acetate |             |
| Freshwater                |               | 0,26 mg/l   |
| Marine water              |               | 0,026 mg/l  |
| Freshwater sediment       |               | 0,34 mg/kg  |
| Marine sediment           |               | 0,034 mg/kg |
| Soil                      |               | 0,22 mg/kg  |

#### 8.2. Exposure controls



##### Protective and hygiene measures

Do not eat, drink, smoke or sneeze at the workplace. Wash hands before breaks and after work. Before starting work, apply solvent-resistant skincare preparations.

##### Eye/face protection

Tightly sealed safety glasses.

##### Hand protection

Test suitability of gloves before use.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Suitable material: Butyl caoutchouc (butyl rubber)

Thickness of the glove material : 0,5 mm

Breakthrough time (maximum wearing time) :  $\geq$  1 h

##### Skin protection

When handling with chemical substances, protective clothing with CE-labels including the four control digits must be worn.

##### Respiratory protection

Respiratory protection necessary at: insufficient ventilation. With correct and proper use, and under normal conditions, breathing protection is not required. If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Combination filtering device (EN 14387) Use the following filter types for cleaning waste gases: A-P2

##### Environmental exposure controls

Do not allow to enter into soil/subsoil. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state: liquid  
 Colour: light yellow  
 Odour: ester

#### Test method

pH-Value: Test not required.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 250.2103 Extra - Fix Slow (TF) All Purpose Adhesive

Print date: 07.10.2015

Product code: 250.2103

Page 7 of 12

#### Changes in the physical state

|  |                        |            |
|--|------------------------|------------|
| Initial boiling point and boiling range: | 65-95 °C               | DIN 53 171 |
| Flash point:                             | -18 °C                 | DIN 51 755 |
| Lower explosion limits:                  | 1 vol. %               |            |
| Upper explosion limits:                  | 11,5 vol. %            |            |
| Ignition temperature:                    |                        | DIN 51 794 |
| Vapour pressure:<br>(at 20 °C)           | 175 hPa                | DIN EN 12  |
| Vapour pressure:<br>(at 50 °C)           | 950 hPa                |            |
| Density (at 20 °C):                      | 0,81 g/cm <sup>3</sup> | DIN 51 757 |
| Viscosity / dynamic:<br>(at 20 °C)       | 1200-1800 mPa·s        | DIN 51550  |
| Solvent separation test:                 | < 0,1 %                |            |
| Solvent content:                         | 79,00 %                |            |

#### 9.2. Other information

|                |         |
|----------------|---------|
| Solid content: | 21,00 % |
|----------------|---------|

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

The study does not need to be conducted because the substance is known to be stable at room temperature for prolonged periods of time (days).

#### 10.2. Chemical stability

The study does not need to be conducted because the substance is known to be stable at room temperature for prolonged periods of time (days).

#### 10.3. Possibility of hazardous reactions

Gas/vapour, highly flammable.

#### 10.4. Conditions to avoid

Decomposition takes place from temperatures above: > 150 °C

#### 10.5. Incompatible materials

Acid, concentrated. , Oxidizing agents, strong.

#### 10.6. Hazardous decomposition products

Thermal decomposition can lead to the escape of irritating gases and vapours.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

##### Toxicokinetics, metabolism and distribution

There are no data available on the preparation/mixture itself.

##### Acute toxicity

Based on available data, the classification criteria are not met.

There are no data available on the preparation/mixture itself.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 250.2103 Extra - Fix Slow (TF) All Purpose Adhesive

Print date: 07.10.2015

Product code: 250.2103

Page 8 of 12

| CAS No     | Chemical name   |        |             |         |        |
|------------|---|--------|-------------|---------|--------|
|            | Exposure routes   | Method | Dose        | Species | Source |
| 64742-49-0 | Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha |        |             |         |        |
|            | oral  | LD50   | 5000 mg/kg  | Rat     |        |
|            | dermal  | LD50   | 3160 mg/kg  | Rabbit  |        |
|            | inhalative (4 h) vapour   | LC50   | 25 mg/l     | Rat     |        |
| 141-78-6   | ethyl acetate   |        |             |         |        |
|            | oral  | LD50   | 5600 mg/kg  | Rat     |        |
|            | dermal  | LD50   | 18000 mg/kg | Rabbit  |        |
|            | inhalative (4 h) vapour   | LC50   | 58 mg/l     | Rat     |        |
| 110-82-7   | cyclohexane   |        |             |         |        |
|            | oral  | LD50   | 12705 mg/kg | Rat     |        |
|            | dermal  | LD50   | 2000 mg/kg  | Rabbit  |        |
|            | inhalative (4 h) vapour   | LC50   | 20 mg/l     | Rat     |        |
| 8052-10-6  | Rosin, colophony  |        |             |         |        |
|            | oral  | LD50   | 2000 mg/kg  | Rat     |        |
|            | dermal  | LD50   | 2000 mg/kg  | Rabbit  |        |

#### Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

Frequently or prolonged contact with skin may cause dermal irritation.

#### Sensitising effects

Based on available data, the classification criteria are not met.

May cause sensitization by inhalation and skin contact. Kolophonium

#### STOT-single exposure

May cause drowsiness or dizziness. (ethyl acetate), (cyclohexane)

#### Severe effects after repeated or prolonged exposure

Repeated exposure may cause skin dryness or cracking.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Inhalation causes narcotic effects/intoxication.

#### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

There are no data available on the preparation/mixture itself.

#### Aspiration hazard

Based on available data, the classification criteria are not met.

#### Specific effects in experiment on an animal

There are no data available on the preparation/mixture itself.

## SECTION 12: Ecological information

### 12.1. Toxicity

Longterm fish toxicity Product is easily volatile. Product is slightly soluble in test vehicle. An aqueous dispersion has been tested.



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 250.2103 Extra - Fix Slow (TF) All Purpose Adhesive

Print date: 07.10.2015

Product code: 250.2103

Page 9 of 12

| CAS No     | Chemical name   |        |           |           |                          |        |
|------------|---|--------|-----------|-----------|--------------------------|--------|
|            | Aquatic toxicity  | Method | Dose      | [h]   [d] | Species                  | Source |
| 64742-49-0 | Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha |        |           |           |                          |        |
|            | Acute fish toxicity   | LC50   | 10 mg/l   | 96 h      | Fisch                    |        |
|            | Acute algae toxicity  | ErC50  | 10 mg/l   | 72 h      | Alge                     |        |
|            | Acute crustacea toxicity  | EC50   | 10 mg/l   | 48 h      | Daphnie                  |        |
| 141-78-6   | ethyl acetate   |        |           |           |                          |        |
|            | Acute fish toxicity   | LC50   | 230 mg/l  | 96 h      | Pimephales promelas      |        |
|            | Acute algae toxicity  | ErC50  | 3300 mg/l | 72 h      | Scenedesmus subspicatus  |        |
|            | Acute crustacea toxicity  | EC50   | 717 mg/l  | 48 h      | Daphnia magna            |        |
| 110-82-7   | cyclohexane   |        |           |           |                          |        |
|            | Acute fish toxicity   | LC50   | 55 mg/l   | 96 h      | Leuciscus idus melanotus |        |
|            | Acute algae toxicity  | ErC50  | 500 mg/l  | 72 h      | Desmodesmus subspicatus  |        |
|            | Acute crustacea toxicity  | EC50   | 0,9 mg/l  | 48 h      | Daphnia magna            |        |

#### 12.2. Persistence and degradability

Product is biodegradable with difficulty.

#### 12.3. Bioaccumulative potential

There are no data available on the preparation/mixture itself.

##### Partition coefficient n-octanol/water

| CAS No     | Chemical name   | Log Pow |
|------------|---|---------|
| 64742-49-0 | Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha | 4-5     |
| 141-78-6   | ethyl acetate   | 0,6     |
| 110-82-7   | cyclohexane   | 3,4     |

##### BCF

| CAS No   | Chemical name | BCF | Species | Source |
|----------|---------------|-----|---------|--------|
| 141-78-6 | ethyl acetate | 30  |         |        |

#### 12.4. Mobility in soil

There are no data available on the preparation/mixture itself.

#### 12.5. Results of PBT and vPvB assessment

There are no data available on the preparation/mixture itself.

#### 12.6. Other adverse effects

Toxic to aquatic life with long lasting effects.

#### Further information

Do not let product enter drains.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

##### Advice on disposal

Consult the appropriate local waste disposal expert about waste disposal.

##### Waste disposal number of waste from residues/unused products

080406 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products)

##### Waste disposal number of used product

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 250.2103 Extra - Fix Slow (TF) All Purpose Adhesive

Print date: 07.10.2015

Product code: 250.2103

Page 10 of 12

080406 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products)

#### Waste disposal number of contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

#### Contaminated packaging

Completely emptied packages can be recycled.

### SECTION 14: Transport information

#### Land transport (ADR/RID)

**14.1. UN number:** UN1133  
**14.2. UN proper shipping name:** Adhesives (Cyclohexane)  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
 Hazard label: 3



Classification code: F1  
 Limited quantity: 5 L  
 Excepted quantity: E1  
 Transport category: 3  
 Hazard No: 33  
 Tunnel restriction code: D/E

#### Other applicable information (land transport)

Additional information on classification : 2.2.3.1.4 ADR / GGVSEB

#### Inland waterways transport (ADN)

**14.1. UN number:** UN1133  
**14.2. UN proper shipping name:** Adhesives (Cyclohexane)  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
 Hazard label: 3



Classification code: F1  
 Limited quantity: 5 L  
 Excepted quantity: E1

#### Other applicable information (inland waterways transport)

Additional information on classification : 2.2.3.1.4 ADR / GGVSEB

#### Marine transport (IMDG)

**14.1. UN number:** UN1133  
**14.2. UN proper shipping name:** Adhesives (Cyclohexane)  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 250.2103 Extra - Fix Slow (TF) All Purpose Adhesive

Print date: 07.10.2015

Product code: 250.2103

Page 11 of 12

Hazard label: 3



Special Provisions: 223, 955  
 Limited quantity: 5 L  
 Excepted quantity: E1  
 EmS: F-E, S-D

#### Other applicable information (marine transport)

Category: A  
 Staukategorie A  
 Additional information on classification : 2.3.2.2 IMDG-Code

#### Air transport (ICAO)

**14.1. UN number:** UN 1133  
**14.2. UN proper shipping name:** Adhesives  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
 Hazard label: 3



Special Provisions: A3  
 Limited quantity Passenger: 10 L  
 Passenger LQ: Y344  
 Excepted quantity: E1  
 IATA-packing instructions - Passenger: 355  
 IATA-max. quantity - Passenger: 60 L  
 IATA-packing instructions - Cargo: 366  
 IATA-max. quantity - Cargo: 220 L

#### Other applicable information (air transport)

E3  
 : Y344  
 E1

#### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: yes



### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### EU regulatory information

2004/42/EC (VOC): 100 % (810 g/l)

##### Additional information

Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).  
 Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## 250.2103 Extra - Fix Slow (TF) All Purpose Adhesive

Print date: 07.10.2015

Product code: 250.2103

Page 12 of 12

### National regulatory information

Employment restrictions: Observe employment restrictions for young people. Observe employment restrictions for child bearing mothers and nursing.

Water contaminating class (D): 2 - water contaminating

### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

## SECTION 16: Other information

### Changes

This data sheet contains changes from the previous version in section(s): 2,3.

### Relevant H and EUH statements (number and full text)

|        |  |
|--------|--|
| H225   | Highly flammable liquid and vapour.                          |
| H304   | May be fatal if swallowed and enters airways.                |
| H315   | Causes skin irritation.                                      |
| H317   | May cause an allergic skin reaction.                         |
| H319   | Causes serious eye irritation.                               |
| H336   | May cause drowsiness or dizziness.                           |
| H400   | Very toxic to aquatic life.                                  |
| H410   | Very toxic to aquatic life with long lasting effects.        |
| H411   | Toxic to aquatic life with long lasting effects.             |
| EUH018 | In use may form flammable/explosive vapour-air mixture.      |
| EUH066 | Repeated exposure may cause skin dryness or cracking.        |
| EUH208 | Contains Rosin, colophony. May produce an allergic reaction. |

### Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

---

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*